



DIN Rail

D-TERMO4

4 outputs programmable thermostat

Technical data

Power suppl	110/230 V ~ 50/60 Hz
Consumption	< 0.5 W
Maximum current	5 A cos Φ = 1
	2.5 A cos Φ = 0.4
Maximum voltage on contacts	230 V~
Ingress protection IP	IP20

Description

The D-TERMO4 is a programmable thermostat to control air flow units with 2 tubes. It allows the control of 3 ventilation speeds and the heating or cooling valve. This control is made with 4 contacts with a common point that can be low voltage or 230 V.

The D-TERMO4 needs the information about temperature from an external command. Therefore it can be used with a touch panel OT-T6S_/OT-T4S_ installed on a C_OUT_, C-1SHU, C-IN_ or alternatively as an actuator programmed as slave of a C-TERMO4/C-CLIMA4.

Applications


Control of climatization by 2 tubes in homes, shops, hospitals, clinics and hotels.

Installation

The D-TERMO4 is made for DIN rail mounting, occupying 2 modules of 17.5 mm.

Features

- 3 speed ventilation control
- Valve control for heating / cooling



Danger - Electric Shock Risk!

Switch off the power before any intervention.

Handling by qualified and authorized persons only.


Subject to change without notice



DIN Rail D-TERMO4

4 outputs programmable thermostat

Installation Schematic:



Danger - Electric Shock Risk!
 Switch off the power before any intervention.
 Handling by qualified and authorized persons only.

Subject to change without notice