




Technical Details



Only Touch

OT-T4S

Touch panel with combined thermostat and automation 8 touch buttons.

Technical data

Power supply:

From wall command: C-_OUT_/C-1SHU_ /C-IN_/C-2MOT-RF/C-010V/C-1DIM (+24 V) Ingress protection IP

Description

The OT-T4S_ is touch panel with 8 illuminated sensors holding a sensor of temperature.

There are 4 specific keys for climate control, when associated with air conditioning modules of type C-TERMO_, C-TERMO4_, C-CLIMA_, C-CLIMA4_, D-8TERMO or D-_TERMO. The remaining keys are used for general automation control.

The buttons light up to the touch, displaying the current room temperature. When the temperature is reset, it shows the new temperature chosen for 2.5 seconds.

Applications

Climatization control. Lights and shutters control.

Installation


The OT-T4S_ is mounted on the C-_OUT_/C-1SHU_ /C-IN_/C-2MOT-RF/C-010V/C-1DIM commands.

Available Units

		Color		Finish Coat		Buttons	
Name	White	Silver	Black	Mate	Glossy	General	Shutters
OT-T4S-GW	✓			✓		✓	
OT-T4S-GS		✓		✓		✓	
OT-T4S-GB			✓	✓		✓	
OT-T4S-SW	✓			✓			4
OT-T4S-SS		✓		✓			1
OT-T4S-SB			✓	✓			V
OT-T4S-GWG	✓				✓	✓	
OT-T4S-GSG		V			✓	4	
OT-T4S-GBG			V		√	4	
OT-T4S-SWG	√				√		√
OT-T4S-SSG		4			√		V
OT-T4S-SBG			√		✓		✓

Features

8 touch-sensitive touch sensors Temperature indication from 18 to 24° C Built-in temperature sensor





Subject to change without notice



Danger - Electric Shock Risk! Switch off the power before any intervention.

Handling by qualified and authorized persons only.

Enancer Electrónica, Lda

Rua Max Grundig, 9 4705-820 Braga Portugal Tel: +351 253 221 484 info@only-smartbuildings.com












Technical Details




Only Touch

OT-T4S_

Touch panel with combined thermostat and automation 8 touch buttons.

Connection Diagram:





Danger - Electric Shock Risk! Switch off the power before any intervention.

Handling by qualified and authorized persons only.

Subject to change without notice