




Technical Details



Only Touch OT-TERMO

Touch panel thermostat without display

Technical data

Power supply:		
From wall command:	C-TERMO_/C-	
TERMO4_ (+24 V)		
Ingress protection IP		IP20

Description

The OT-TERMO_ is touch panel with 4 illuminated sensors for chrono thermostats like C-TERMO_ or C-TERMO4_

The OT-TERMO_ buttons illuminates when touched, showing the actual temperature of the room. When the target temperature is changed, it shows the selected temperature for 2.5 seconds, returning then automatically to the selected temperature.

Applications

Climatization commands: C-TERMO_/C-TERMO4_. Climatization control.

Installation

The OT-TERMO_ is mounted on the C-TERMO_ or C-TERMO4_ commands.

Units available


		Color		Finish Coat	
Name	White	Silver	Black	Matte	Glossy
OT-TERMO-W	\checkmark			\checkmark	
OT-TERMO-S		\checkmark		\checkmark	
OT-TERMO-B			<	\checkmark	
OT-TERMO-WG	\checkmark				\checkmark
OT-TERMO-SG		\checkmark			\checkmark
OT-TERMO-BG			\checkmark		\checkmark

Features

4 illuminated touch buttons

Temperature indication between 20 and 24ºC.

Temperature sensor incorporated





Danger - Electric Shock Risk! Switch off the power before any intervention. Handling by qualified and authorized persons only.

Subject to change without notice

Enancer Electrónica, Lda Rua Max Grundig, 9 4705-820 Braga Portugal Tel: +351 253 221 484 info@only-smartbuildings.com


www.only-smartbuildings.com

COMPETE 2020 PORTUGAL 2020 Control And Engrav






Technical Details



Only Touch OT-TERMO_

Touch panel thermostat without display

Connection Diagram:



OT-TERMO

Danger - Electric Shock Risk! Switch off the power before any intervention. Handling by qualified and authorized persons only.

Enancer Electrónica, Lda Rua Max Grundig, 9 4705-820 Braga Portugal Tel: +351 253 221 484 info@only-smartbuildings.com Subject to change without notice