




Technical Details



In Wall C-1SHU

1 channel 230V~ window shutter actuator

Technical data

Power supply Power consumption	110/230V~ 50/60Hz < 0.5W
Contact rating: Resistive load Max. switching voltage Max. switching current Max. switching power	8A 250VAC 440VAC 8A 2000VA
Ingress protection IP	IP20

Description

The C-1SHU is a 230V~ window shutter actuator. It can be fitted with any Only wall Keypad $^{(1)(2)}.$

Applications

Actuator for 230V~ shutters, sunscreens, blinds, curtains, projection screens and blackouts at homes, shops, hospitals, clinics and hotels.

Installation

The C-1SHU is to be mounted in flush-mounting electrical box (60mm between fixing points).


Features

8A relay output

Local operation even without BUS connection Status indication by LED Push-wire terminal connections with derivation Open and close time independently configured for scenario positioning

Up to 28 buttons can be stored in the internal non-volatile memory

 $\ensuremath{\mathsf{Operation}}$ modes: Toggle, Up, Down, Timer, Delay and Scenario, depending on the received command



Ŵ

Danger - Electric Shock Riskl Switch off the power before any intervention. Handling by qualified and authorized persons only.

⁽¹⁾ Not compatible with OT-CLIMA-XY, OT-CLIMAA-XY, OT-FM-XY, OT-FMA-XY, OT-16S-XY and OT-16SD-XY ⁽²⁾ C-1SHU must have firmware version \geq to V4.0 to work with OT-MF-XY

Subject to change without notice

C-1SHU_R06

Enancer Electrónica, Lda Rua Max Grundig, 9 4705-820 Braga Portugal Tel: +351 253 221 484 info@only-smartbuildings.com

www.only-smartbuildings.com

COMPETE 2020 PORTUGAL 2020 Concernent Index Inde